

PROWELD is a zinc aluminium welding primer, suitable for repairing damaged galvanising. It provides outstanding corrosion protection and is resistant to high temperatures.


Suitable substrates (cleaned & abraded)

Physical and chemical data


Basis of binder	Acrylic
Colour	Grey
Coverage	1m ²
Temperature resistance	Up to 90°C
Storage stability	10 years in appropriate storage (-10°-25°C, relative air humidity of max. 60%)
Size	500ml
VOC content	340g/500ml

Application guide

- Carry out test spray
- Areas to be sprayed must be free of grease, dust and dry
- For professional use only
- Wear an appropriate respirator




Before use, shake the aerosol for 2 minutes and spray a sample area.



Apply in cross coats from distance of 250mm from object




2-3 coats @ 40-60µm



Air dry 45 minutes @ 20°C
Overcoatable 20 minutes wet on wet



5-8 Minutes



After use, turn aerosol upside down and empty valve

Features and benefits

- Weld through primer with excellent adhesion
- Very good cathodic corrosion prevention
- Resistant to petrol, chemicals and weather influences
- Compatible with SPOT, MIG and TIG welding methods
- Supplied with 2 nozzles

Environmentally sound

The products supplied by ProXL are 100% free of heavy metals and the caps and packaging are made of recyclable material.

Disposal

Completely emptied cans should be put in recycling skips or appropriate container. Cans which are not empty should be disposed of as special refuse.

This application and technical information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively is the responsibility of the user.



DISCLAIMER OF LIABILITY

The information contained in this Technical Data Sheet is correct to the best of Alpha Coatings Limited trading as Capella Solutions Group's ("Capella") knowledge, however, you must satisfy yourselves that the Goods are suitable for your needs by way of your independent testing or other processes. Capella makes no warranty, representation, or guarantee regarding the information contained in the Technical Data Sheet or the suitability of its products and services for any particular purpose, nor does Capella assume liability arising out of the application or use of the Goods other than any liability which cannot be limited by law including but not limited to liability for: (a) death or personal injury caused by negligence; (b) fraud or fraudulent misrepresentation; and (c) breach of the terms implied by section 12 of the Sales of Goods Act 1979, in such circumstances Capella's total liability shall not exceed the cost of the Goods. Capella's total liability includes liability in contract, tort, negligence, breach of statutory duty, or otherwise. It is the Customer's responsibility to ensure that the guidance on the Technical Data Sheet is followed.